



Vehicle	AUDI / A8 3.0 TDI quattro / 01/2004 - / Двухобъемный лимузин, Вездеходный, Нормальн.и удлиненная база а/м
Country of manufacture	D
Cubic capacity/Power	3.0 / 171 kW
Motor tag	ASB
RB key	AUD 1232

Lubricants and capacities

Engine oil options

Ambient temperature range	: All temperatures
Engine oil grade	SAE: 0W/30
(1) Engine oil classification	OEM: VW 506.01
Ambient temperature range	: All temperatures
Engine oil grade	SAE: 5W/30
(2) Engine oil classification	OEM: VW 507.00
Ambient temperature range	: All temperatures
Engine oil grade	SAE: 5W/30, 5W/40
Engine oil classification	OEM: VW 505.00
Ambient temperature range	: -20°C->15°C
Engine oil grade	SAE: 5W/30, 5W/40
Engine oil classification	OEM: VW 505.01
Ambient temperature range	: All temperatures
Engine oil grade	SAE: 5W/50
Engine oil classification	OEM: VW 505.01
Ambient temperature range	: All temperatures
Engine oil grade	SAE: 10W/30, 10W/40
Engine oil classification	OEM: VW 505.00
Ambient temperature range	: -20°C->15°C
Engine oil grade	SAE: 10W/30, 10W/40
Engine oil classification	OEM: VW 505.01
Ambient temperature range	: All temperatures
Engine oil grade	SAE: 10W/50, 10W/60
Engine oil classification	OEM: VW 505.01
Ambient temperature range	: -15°C->40°C
Engine oil grade	SAE: 15W/40, 15W/50
Engine oil classification	OEM: VW 505.01
Ambient temperature range	: -15°C->40°C
Engine oil grade	SAE: 20W/40, 20W/50
Engine oil classification	OEM: VW 505.01
Engine with filter(s)	litres: 8,2

Other lubricants and capacities

Automatic transmission fluid	Type: G 055 005 A2
Differential oil grade - front	SAE: 75W/90 Synthetic
Differential front/AT	litres: 1,1
Differential oil grade - rear	SAE: 75W/90

Differential rear	litres: 1,5
Transfer box oil grade	SAE: 75W/90 Synthetic
Transfer box	litres: 0,55
Brake fluid	Type: DOT 4
Brake fluid	litres: 1,0
Power steering fluid	Type: G 002 000

Important note

(1)

Longlife service:

PD engine = VW 506.01

TDI engine = VW 506.00

(2)

Only on engines with diesel particulate filters (DPF).

Low ash engine oil MUST be used to ensure long service life of diesel particulate filter (DPF).